# SENIN ASYM

KLARIS



## Up to 131 lm/W
## L80 B10 100.000h

Instructions of use and Declaration of conformity:
https://klaris.ro/en/product/senin/

## Standard:

LED | IP20 | IK03 | 220 -240V 50/60Hz | CL I | 650° | CE | RoHS compliant


## Options:

DIM








| | L | W | H |
|---|---|---|---|
| SENIN ASYM L1200 | 1196 | 146 | 89 |
| SENIN ASYM L1500 | 1496 | 146 | 89 |

| TYPE | optic | CRI | CCT | Flux (lm) | Total Power (W) | Efficacy lm/W | UGR | TA | WEIGHT kg | unit / cart | unit /palet |
|---|---|---|---|---|---|---|---|---|---|---|---|
| SENIN LED ASYM L1200 3340/830 | ASYM | 80 | 3000 | 3340 | 27 | 125 | - | +10°C / +40°C | 3.7 | 1 | 62 |
| SENIN LED ASYM L1200 3500/840 | ASYM | 80 | 4000 | 3500 | 27 | 131 | - | +10°C / +40°C | 3.7 | 1 | 62 |
| SENIN LED ASYM L1500 4870/830 | ASYM | 80 | 3000 | 4870 | 41.0 | 119 | - | +10°C / +40°C | 4.5 | 1 | 62 |
| SENIN LED ASYM L1500 5100/840 | ASYM | 80 | 4000 | 5100 | 41.0 | 124 | - | +10°C / +40°C | 4.5 | 1 | 62 |