

SENIN

KLARIS







Up to 143 lm/W
L80 B10 70.000h


Instructions of use and Declaration of conformity:
https://klaris.ro/en/product/senin/


Standard:

LED	IP20	IK07
220 -240V 50/60Hz	CL I	650°
CE	RoHS compliant	HCL

Options:

DIM	COOL WHITE	M 675 x675
CRI90		M 625 x625
110 -277V 50/60Hz		WIEL





	L	W	H
SENIN LED M600X600	596	596	57
SENIN LED M1200X300	1196	296	57
SENIN LED M1500X300	1496	296	57

SENIN

KLARIS

TYPE	optic	CRI	CCT	Flux (lm)	Total Power (W)	Efficacy lm/W	UGR	TA	WEIGHT kg	unit / cart	unit /palet
SENIN LED M600X600 2 3880/830 DPB	DPB	80	3000	3880	31.5	123	<19	+10°C / +40°C	3.7	1	50
SENIN LED M600X600 2 4070/840 DPB	DPB	80	4000	4070	31.5	129	<19	+10°C / +40°C	3.7	1	50
SENIN LED M600X600 3 3010/830 DPB	DPB	80	3000	3010	23.0	131	<19	+10°C / +40°C	3.6	1	60
SENIN LED M600X600 3 3160/840 DPB	DPB	80	4000	3160	23.0	137	<19	+10°C / +40°C	3.6	1	60
SENIN LED M600X600 4 4200/830 DPB	DPB	80	3000	4200	31.7	132	<19	+10°C / +40°C	3.7	1	60
SENIN LED M600X600 4 4400/840 DPB	DPB	80	4000	4400	31.7	139	<19	+10°C / +40°C	3.7	1	60
SENIN LED M1200X300 2 4080/830 DPB	DPB	80	3000	4080	30.0	136	<19	+10°C / +40°C	3.7	1	50
SENIN LED M1200X300 2 4290/840 DPB	DPB	80	4000	4290	30.0	143	<19	+10°C / +40°C	3.7	1	50
SENIN LED M1500X300 2 6740/830 DPB	DPB	80	3000	6740	50.0	135	<19	+10°C / +40°C	4.5	1	50
SENIN LED M1500X300 2 7070/840 DPB	DPB	80	4000	7070	50.0	141	<19	+10°C / +40°C	4.5	1	50